

Crude Naphthalene

Product Datasheet

Naphthalene is an organic compound extracted during coal tar distillation. Typical naphthalene is 10% by weight in coal tar. Distillation of coal tar yields an oil containing about 50% naphthalene along with 12 other aromatic compounds. After being washed with aqueous sodium hydroxide/sulphuric acid to remove acidic components (chiefly various phenols), and removing basic components, this oil undergoes fractional distillation to isolate naphthalene. The crude naphthalene resulting from this process is about 95%-97% naphthalene by weight.

APPLICATIONS

- ◆ Used in fine chemicals and pharmaceutical processes to produce beta naphthol phthalic anhydride
- ◆ Used in sulphonated naphthalene and tanning agents
- ◆ Used in making disinfectants for household usage
- ◆ Used for organic synthesis including dye production

PERFORMANCE

- ◆ High naphthalene content leads to a better yield of sulphonated naphthalene and tanning agents

TYPICAL QUALITY PROPERTIES

Property	Unit	Specification
Crystallization Point	°C	77.5Min.
Appearance (Flakes)	-	Off White colour
Moisture content	%	0.2 Max
Ash Content	%	0.02 Max
Matter insoluble in benzene	%	0.5 Max
Quinoline content	PPM	200 Max

PACKAGING

Packing Type	Quantity
PP Bag with Liner	40 Kg



Know more about
our coal tar
derivatives products

TECHNICAL AND SALES CONTACT

HEAD OFFICE

Upadrastha House, 48, Dr. V. B. Gandhi Marg, Fort, Mumbai – 400023 INDIA Contact number: +91-22-22712800



enquiry@epsiloncarbon.com